

YANTON®

T-S1 MINI WALKIE-TALKIE



Vibration Function

FREQUENCY
PMR 446MHz
FRS 462.5625-467.7125MHz
LPD 433MHz



Memory Channel 199
Comander
Scrambler
VOX function



ULTRA LIGHT / ULTRA COMPACT

YANTON®

T-S1 MINI WALKIE-TALKIE



FREQUENCY
PMR 446MHz
FRS 462.5625-467.7125MHz
LPD 433MHz

Memory Channel 199
Comander
Scrambler
VOX function

STANDARD ACCESSORIES



SPECIFICATION

GENERAL		TRANSMIT PART	
Frequency Range	VHF: 136~174MHz UHF: 400~480MHz	RF Power	2W
Operating Temperature	-20°C~+60°C	Modulate Mode (W/N)	16KΦF3E, 11KΦF3E
Frequency Combination	Phase lock frequency synthesize	Max. Freq. Deviation (W/N)	<5K / <2.5KHz
Frequency Stability	±2.5ppm	Remain Wave Radiation	<-60dB
Memory Channel	16 Channels	Transmitting Current	≤1300mA
Working voltage	DC 3.7V	RECEIVE PART	
Antenna Impedance	50Ω	Sensitivity	<0.25μV(12dB SINAD)
Operating Mode	Simplex of co-frequency or alien frequency	Squelch Sensitivity	<0.20μV
Dimension	95mm×43mm×26mm	Intermodulation Antijamming	50dB
Weight	150g (Include Battery Pack)	Audio Power output	500mW
		Receiving Current	≤100mA
		Squelch Standby	20mA

Notice: Saving your presence, no additional notice will be sent if specification changes because of technology-improving.

QUANZHOU YANTON ELECTRONICS CO.,LTD. | <http://www.yantonradio.com>