

YANTON®

PROFESSIONAL FM TRANSCEIVER

T-M6



Frequency Band 400-480MHZ;
Output Power 3W;
16 Memory Channels;
DTMF;
Built-in CTCSS/DCS;
VOX Function;

YANTON®

PROFESSIONAL FM TRANSCEIVER



Frequency Band 400-480MHZ;
Output Power 3W;
16 Memory Channels;
DTMF;
Built-in CTCSS/DCS;
VOX Function;

SPECIFICATION

GENERAL		TRANSMIT PART	
Frequency Range	400~480MHz	RF Power	3W
Operating Temperature	-20°C~+55°C	Modulate Mode (W/N)	F3E
Frequency Combination	Phase lock frequency synthesize	Max. Freq. Deviation	≤5KHz
Frequency Stability	±2.5ppm	Remain Wave Radiation	<-60dB
Memory Channel	16 Channels	Transmitting Current	≤1000mA
Working voltage	DC 3.7V	RECEIVE PART	
Antenna Impedance	50Ω	Sensitivity	<0.20μV(12dB SINAD)
Operating Mode	Simplex of co-frequency or alien frequency	Squelch Sensitivity	<0.20μV
Dimension	60*35*10mm	Intermodulation Antijamming	50dB
Weight	96g (Include Battery Pack)	Audio Power output	500mW
		Receiving Current	≤100mA
		Squelch Standby	20mA

Notice: Saving your presence, no additional notice will be sent if specification changes because of technology-improving.